

Colourvista Sample Pot offers a picturesque preview of your exterior and interior walls with your choice of shade. It helps you finalize the shade for interior as well as exterior surfaces. Colourvista Sample Pot's bright colours help you visualize the shade on the wall and feel the mood it can create in your space. Its specially designed rich sheen finish enhances the effectiveness of Colourvista tints – the colourants offering from JSW Paints. A simple 4 step application procedure makes it so easy to use that almost anyone can apply it without the help of an expert

*First of its kind, unique formula design which works on interior as well as exterior surfaces*

**PACK SIZE**



250 ML

**GLOSS LEVEL**



**FEATURES**



- Easy to Use
- Bright Colours
- Low VOC
- Water Based
- Works for Interior & Exterior (shade purpose only)
- Roller Friendly Paint
- Paint & Primer
- Superior Opacity

**SURFACES**



New or well prepared previously painted wall, plastered and prepared masonry surfaces

**CAUTION**



- Do not apply below 10°C or above 45°C
- Do not apply if humidity > 90%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain paint before use
- In case of eye contact, wash with plenty of water, seek medical attention
- Tightly close the lid when not in use and store in a cool, dry place



**DIRECTION FOR USE**

- ROLLER** For best results, use a Short Nap Felt Roller
- DILUTION** Dilute Colourvista Sample Pot with 25% clean water

STEP 1	Shake the pack before use.
STEP 2	Open the lid carefully.
STEP 3	Dilute paint with 25% water.
STEP 4	Apply two coats at an interval of 3-4 hours in an area of 1 sq. ft.



**INFORMATION AND CARE**

**ENVIRONMENTAL HEALTH AND SAFETY**

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use disposable rubber gloves, dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

**PRODUCT INFORMATION**

Colours	White
Tint Bases	CV-1, CV-3, CV-4, CV-Y, CV-M

**KEY DATA**

No. of colours	1808 shades (Ask for Colourvista Shade Panorama fandeck)
Coverage^	Suitable for making patch application of 2 to 4 sq feet per pack.
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	9 - 12 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (upto 25%)
VOC levels~	<20 gms/L



## JSW Paints Top Coats Range:

Our extensive range of water based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



PIXA CLASSIC  
JOY



HALO MAJESTIC  
INTERIORS



HALO MAJESTIC  
EXTERIORS



PIXA ELEGANT  
INTERIORS



PIXA ELEGANT  
EXTERIORS



AURUS REGAL  
INTERIORS



AURUS REGAL  
EXTERIORS



HALO AQUAGLO  
GLOSS



HALO AQUAGLO  
SATIN



JSW Paints presents Colourvista, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988