



# Halõ

MAJESTIC INTERIORS



Halo Majestic Interiors Silk, is a state of the art Emulsion for Interior walls with a silk finish where design expertise offers best-in-class quality with low VOC. This water-based-100% pure acrylic emulsion delivers excellent durability, washability and stain resistance to bring the promise of long lasting beauty alive.

Experience Halo Majestic Interiors Silk -  
*Carefully crafted for an incredibly smooth finish.*

## PACK SIZES



## GLOSS LEVEL



## FEATURES

Paint & Primer  
Low VOC  
Excellent Stain Resistance  
Antifungal  
Endures 7 Years

Superior Opacity  
Elegant Sheen  
Excellent Smooth Finish  
Fast and Easy to Finish  
Roller Friendly Paint

## CAUTION

Do not apply below 10°C or above 45°C  
Do not apply if humidity > 90%  
Do not over-thin. Use thinned paint within 24 hours  
Shake, stir and strain paint before use  
In case of eye contact, wash with plenty of water  
Tightly close the lid when not in use and store in a cool, dry place

## CERTIFICATION

Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>  
Compliant to GRIHA standards for Low VOC<sup>2</sup>  
Compliant to JIS test for Anti-Microbial Activity<sup>3</sup>  
No Fungal Growth as per ASTM Test D5590:2017<sup>4</sup>  
Resistance to Household Stains as per ASTM Test D4828:94(2016)<sup>5</sup>



## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure for 28 days before application
- Cured plaster should be hard (non powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a Structural Engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement/acrylic putty (wherever needed) to fill the dents and level the surface
- Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application



## APPLICATION

**ROLLER** For best results, use a Short Nap Felt Roller  
**DILUTION** Dilute Halo Majestic Interiors with 25% clean water

For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT	Halõ MAJESTIC INTERIORS	4 hrs dry
STEP 2	SECOND COAT	Halõ MAJESTIC INTERIORS	4 hrs dry

For new masonry surface^:

STEP 1	1 COAT	Wall Primer INTERIORS	3-4 hrs dry
STEP 2	2 COATS	Wall Putty ACRYLIC BASED	6-8 hrs dry before re-coat
STEP 3	1 COAT	Wall Primer INTERIORS	3-4 hrs dry
STEP 4	2 COATS	Halõ MAJESTIC INTERIORS	4 hrs dry before re-coat



## PAINT & PRIMER

Halo Majestic Interiors is specially formulated to blend the functions of a primer with the finish coat. Two coats of Halo Majestic Interiors provides a sturdier coat that the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.\*

\*When painting unpainted surfaces, light shade over previous dark shade, painting over oil based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Apply JSW Interior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before finish coat.



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

### POST PAINTING CARE

- Always remove any wall stains immediately from the walls
- Remove all dirt using a clean cloth or duster. Always remove dirt from top to bottom. This helps in avoiding loose dirt to smudge the walls
- For household stains like pencil, tea, coffee, crayons, turmeric, ketchup, sketch pen etc., use liquid dish wash/mild detergent solution. Use a sponge to remove the stains. Wipe the area with a clean cloth

## PRODUCT INFORMATION

Colours	White
Tint Bases	HI-1, HI-3, HI-4, HI-V, HI-M

### KEY DATA

No. of colours	1808 shades (Ask for Colourvista Shade Panorama fandeck)
Coverage <sup>^</sup>	140 - 160 sq.ft./L/2 coats 13 - 14.9 m <sup>2</sup> /L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	9 - 12 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (upto 25%)
VOC levels~	<10 gms/L

## Other Haló products:

JSW Paints Halo Range offers best-in-class emulsions for Exterior Walls, eco-friendly water based enamels - Aquaglo for Wood & Metal and Fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel, Halo Aquaglo Majestic Gloss is designed to create a range of looks that are immaculate, impressive and truly beautiful. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - **Think Beautiful.** Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

<sup>1</sup>Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. <sup>2</sup>Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai. <sup>3</sup>Compliant to Japanese Industrial Standard - JIS Z 2801: 2010 'Test for Anti-Bacterial Activity and Efficacy' as tested at Biotech Testing Services, Mumbai. <sup>4</sup>No fungal growth when tested as per ASTM D5590: 2017 for 'Determining the Resistance of Paint Films to Fungal Defacement' as tested at Biotech Testing Services, Mumbai. <sup>5</sup>Resistance to stains when tested as per ASTM D4828: 94 (2012) for relative ease of removal of common soil and stains from interior coatings as tested at National Test House, Mumbai.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988



# Halõ

MAJESTIC EXTERIORS



Halo Majestic Exteriors Silk, is an excellent emulsion for exterior walls with a silk finish which provides an active defense against algae, fungus, cracking, peeling and dirt pick up for exteriors, and provides the best-in-class weather resistance. So that your freshly painted exterior stays looking new even in extreme weather and sunlight year after year.

Experience Halo Majestic Exteriors Silk -  
*Carefully crafted for long-lasting protection.*

### PACK SIZES



### GLOSS LEVEL



### FEATURES

- Paint & Primer
- Low VOC
- Anti-Algal
- Anti-Fungal
- Dust Resistant
- Endures 7 Years
- Superior Opacity
- Excellent Colour Retention
- Fast and Easy to Finish
- Roller Friendly Paint

### CAUTION

- Do not apply below 10°C or above 45°C
- Do not apply if humidity > 90%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain paint before use
- In case of eye contact, wash with plenty of water
- Tightly close the lid when not in use and store in a cool, dry place

### CERTIFICATION

- Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>
- No Algal growth as per ASTM Test D5589-09 (2013)<sup>2</sup>
- UV Block as per QUV Test<sup>3</sup>



## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure for 28 days before application
- Cured plaster should be hard (non-powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a Structural Engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement putty (wherever needed) to fill the dents and level the surface
- Wipe clean before paint application



## APPLICATION

- ROLLER** For best results, use a Long Nap Felt Roller
- DILUTION** Dilute Halo Majestic Exteriors Silk with 25% clean water

### For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT	Halõ MAJESTIC EXTERIORS	4 hrs dry
STEP 2	SECOND COAT	Halõ MAJESTIC EXTERIORS	4 hrs dry

### For new masonry surface^:

STEP 1	1 COAT	Wall Primer EXTERIORS	3-4 hrs dry
STEP 2	2 COATS	Halõ MAJESTIC EXTERIORS	4 hrs dry before re-coat



## PAINT & PRIMER

Halo Majestic Exteriors is specially formulated to blend the functions of a primer with the finish coat. Two coats of Halo Majestic Exteriors provides a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.\*

\*When painting unpainted surfaces, light shade over previous dark shade, painting over cement paint - a coat of JSW Exterior Wall Primer should be applied. Apply JSW Exterior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before finish coat.



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

### POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants and trees near the painted surface
- Prevent sharp objects or impact that damage the paint film
- Ensure proper cleaning of the surface at an interval of 6 months

## PRODUCT INFORMATION

Colours

White

Tint Bases

HE-1, HE-2, HE-3, HE-4,  
HE-V, HE-M

### KEY DATA

No. of colours

**1808 shades**  
(Ask for Colourv<sup>ista</sup> Shade  
**Panorama** fandeck)

Coverage<sup>^</sup>

**60 - 65 sq.ft./2 coats**  
**5.5 - 6 sqm/2 coats**

Drying Time\*  
(30°C @ 60 R/H)

**Surface Dry - 30 minutes**  
**Recoat - 4 hours**

Flash Point

N/A

Sheen Level

**12 - 15 units @ 60° GH**

Vehicle Type

**Acrylic**

Thin with

**Clean Water (upto 25%)**

VOC levels~

**<10 gms/L**

## Other Halõ products:

JSW Paints Halo Range offers best-in-class emulsions for interior walls, eco-friendly water-based enamels - Aquaglo for Wood & Metal and fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel, Halo Aquaglo Majestic Gloss is designed to create a range of looks that are immaculate, impressive and truly beautiful. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



MAJESTIC INTERIORS



AQUAGLO  
MAJESTIC GLOSS



AQUAGLO  
MAJESTIC SATIN



FRESH  
MAJESTIC FRAGRANCES



JSW Paints presents Colourv<sup>ista</sup> Shade **Panorama**, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourv<sup>ista</sup> Shade **Panorama** Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourv<sup>ista</sup> Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

<sup>1</sup>Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. <sup>2</sup>No algal growth when tested as per ASTM D5589 -09 (2013) for Determining the resistance of Paint Films to Algae Defacement as tested at Biotech Testing Services, Mumbai. <sup>3</sup>Resistance to Ultra Violet Radiation when tested as per ASTM G155: 2013 of paint exposure to Ultra violet radiation generated by Xenon Arc for the duration of 1000 hours as tested at National Test House, Mumbai.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988