



# Halõ

MAJESTIC INTERIORS  
Shine



Halo Majestic Interiors Shine, is a state of the art Emulsion for Interior walls with a satin finish where design expertise offers best-in-class quality with low VOC. This water-based-100% pure acrylic emulsion delivers excellent durability, washability and stain resistance to bring the promise of long lasting beauty alive.

Experience Halo Majestic Interiors Shine -  
*Carefully crafted for rich satin like finish.*

#### PACK SIZES



#### GLOSS LEVEL



#### FEATURES

- Germ Block - Kills 99.9% of bacteria, fungi, and virus Paint & Primer
- Low VOC
- Excellent Stain Resistance
- Antifungal
- Endures 7 Years
- Superior Opacity
- Elegant Sheen
- Excellent Smooth Finish
- Fast and Easy to Finish
- Roller Friendly Paint

#### CAUTION

- Do not apply below 10°C or above 45°C
- Do not apply if humidity > 90%
- Do not over-thin. Use thinned paint within 24 hours
- Shake, stir and strain paint before use
- In case of eye contact, wash with plenty of water
- Tightly close the lid when not in use and store in a cool, dry place

#### CERTIFICATION

- Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>
- Compliant to GRIHA standards for Low VOC<sup>2</sup>
- Compliant to JIS test for Anti-Microbial Activity<sup>3</sup>
- No Fungal Growth as per ASTM Test D5590:2017<sup>4</sup>
- Resistance to Household Stains as per ASTM Test D4828:94(2016)<sup>5</sup>



### PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces
- New plaster or masonry surfaces must be allowed to cure for 28 days before application
- Cured plaster should be hard (non powdery) and in sound condition
- Growths of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water
- In case of areas having excess dampness, please repair the surface before painting
- In case there are structural cracks, please study and repair them with a Structural Engineer
- Open non-structural cracks in V-groove and fill with cement/crack filler
- Apply cement/acrylic putty (wherever needed) to fill the dents and level the surface
- Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application



### APPLICATION

- ROLLER** For best results, use a Short Nap Felt Roller
- DILUTION** Dilute Halo Majestic Interiors with 25% clean water

#### For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT	Halõ MAJESTIC INTERIORS Shine	4 hrs dry
STEP 2	SECOND COAT	Halõ MAJESTIC INTERIORS Shine	4 hrs dry

#### For new masonry surface^:

STEP 1	1 COAT	Wall Primer INTERIORS	3-4 hrs dry
STEP 2	2 COATS	Wall Putty ACRYLIC BASED	6-8 hrs dry before re-coat
STEP 3	1 COAT	Wall Primer INTERIORS	3-4 hrs dry
STEP 4	2 COATS	Halõ MAJESTIC INTERIORS Shine	4 hrs dry before re-coat



### PAINT & PRIMER

Halo Majestic Interiors is specially formulated to blend the functions of a primer with the finish coat. Two\*\* coats of Halo Majestic Interiors provides a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.\*

\*When painting unpainted surfaces, light shade over previous dark shade, painting over oil based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Apply JSW Interior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before finish coat.

\*\*Additional coats may be required for darker shades.



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Use dust mask or nose pad during application, sanding and clean up
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

### POST PAINTING CARE

- Always remove any wall stains immediately from the walls
- Remove all dirt using a clean cloth or duster. Always remove dirt from top to bottom. This helps in avoiding loose dirt to smudge the walls
- For household stains like pencil, tea, coffee, crayons, turmeric, ketchup, sketch pen etc., use liquid dish wash/mild detergent solution. Use a sponge to remove the stains. Wipe the area with a clean cloth

## PRODUCT INFORMATION

Colours	White
Tint Bases	HSI-1, HSI-3, HSI-4, HSI-Y, HSI-M

### KEY DATA

No. of colours	1808 shades (Ask for Colourv <sup>ista</sup> Shade Panorama fandeck)
Coverage <sup>^</sup>	140 - 160 sq.ft./L/2 coats 13 - 14.9 m <sup>2</sup> /L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	17 - 20 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (upto 25%)
VOC levels~	<10 gms/L

## Other Halö products:

JSW Paints Halo Range offers best-in-class emulsions for Exterior Walls, eco-friendly water based enamels - Aquaglo for Wood & Metal and Fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel, Halo Aquaglo Majestic Gloss is designed to create a range of looks that are immaculate, impressive and truly beautiful. Halo Aquaglo Majestic Satin is created to exude a rich-chic feel that works wonders when it comes to creating an ambience that emanates a feeling of elegance and understated opulence. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



JSW Paints presents Colourv<sup>ista</sup> Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourv<sup>ista</sup> Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourv<sup>ista</sup> Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandeck
- Easy to Choose Colour Combinations

<sup>1</sup>Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. <sup>2</sup>Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai. <sup>3</sup>Compliant to Japanese Industrial Standard - JIS Z 2801: 2010 'Test for Anti-Bacterial Activity and Efficacy' as tested at Biotech Testing Services, Mumbai. <sup>4</sup>No fungal growth when tested as per ASTM D5590: 2017 for 'Determining the Resistance of Paint Films to Fungal Defacement' as tested at Biotech Testing Services, Mumbai. <sup>5</sup>Resistance to stains when tested as per ASTM D4828: 94 (2012) for relative ease of removal of common soil and stains from interior coatings as tested at National Test House, Mumbai.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988