



Gap Fix

INTERIORS & EXTERIORS



INTERIOR &
EXTERIOR



JSW Paints Gap Fix Paste is a water based, Ready to use Gap filling paste for interior and exterior surfaces. It provides strong gap filling ability up to 20mm. It is composed of superior quality polymers along with fillers and additives. Its easy to apply, fast dry, light weight abilities make it 100% shrink free.

Its advanced technology gives excellent filling and binding properties and makes it ideal choice.



Pack Size : 650 ML

Upto 20MM

FEATURES



- Gap Filler up to 20MM
- Non Shrinkage
- Multipurpose filler
- Easy To Apply
- Fast Dry
- Best For filling Drilled Holes
- Ready to Paint
- Skin friendly

SURFACES



Internal and external Surfaces Gaps up to 20 MM.



PREPARATION

- Surface Must be free of any dust, Oil, Grease, or other loose particles
- Moisten the surface before applying JSW Gap Fix
- Open up the Crack in V Shaped with Steel Trowel for better application



APPLICATION PROCESS

- For interior Application, Existing Layer of putty needs to be removed till the plaster level
- Apply the JSW Gap Fix, Firmly over crack at single time with putty Knife & level the Surface.
- Use handball application as per convenience while applying the JSW Gap Fix
- Cavities or bubble formation needs to be avoided while application of JSW Gap Fix
- Allow it to completely dry for 24 Hours

PRECAUTION & CARE



- Not for POP Cracks & for Cracks in Putty
- Not recommended for surfaces exposed to Rain
- Not applicable for structural cracks in concrete slabs, or construction joints.
- Do not apply at temperature below 10°C and over 45°C and humidity greater than 90%.
- Tightly close the lid when not in use and store in a cool dry place.
- In Case of Product becomes too dry for application Add potable water in a ratio of 1 Teaspoon to in 250 ml of Gap Fix



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Use a dust mask or nose pad during the application, sanding, and clean up
- Close the container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash the skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic, and other heavy metals

PRODUCT INFORMATION

Colour | White

KEY DATA

Coverage [^]	30-35 running meters per litre at 5 mm depth
Drying Time* (30°C @ 60 R/H)	Surface Dry 1 to 2 Hrs
Sheen Level	NA
Shelf Life	24 months from the date of manufacturing. Store in cool & dry place, away from sun light.

POST PAINTING CARE

- Apply primer coat within 24-48 hrs of putty application
- Apply finishing coat within 7 days of primer application

Other JSW Paints iBlok Products:

JSW Paints preparation range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



iBLOK
ROOF COAT



iBLOK
BASE COAT INTERIOR



iBLOK
BASE COAT EXTERIOR



iBLOK
WATERSTOP 3K



iBLOK
CRACK FIX



iBLOK WATERSTOP
WALL PUTTY

JSW Paints Top Coats Range

Our extensive range of water-based emulsions is designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



MAJESTIC
INTERIORS SILK



MAJESTIC
INTERIORS SHINE



MAJESTIC
EXTERIORS SILK



AURUS
INTERIORS SILK



AURUS
EXTERIORS SILK

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

Version No. 01 (04/2024.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, SA, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988

REFER TO PRODUCT INFORMATION SHEET AND MSDS FOR MORE DETAILS