



Aur^{us}

REGAL EXTERIORS



Aurus Regal Exteriors is a hardwearing emulsion for exterior walls with a matt finish, featuring an advanced formulation that protects the paint against harmful sun rays. It helps prevent damage, providing superior protection for your home against all types of extreme weather conditions, ensuring your home stays beautiful for longer.

Experience Aurus Regal Exteriors - *"Thoughtfully designed for a UV Resistant Finish."*

PACK SIZES



GLOSS LEVEL



FEATURES

- Endures 6 years*
- All Weather Guard
- Anti-Algal
- UV Resistant
- Low VOC
- Paint & Primer*
- Tough and durable film
- Bright Finish
- Fast and easy to finish
- Roller friendly paint
- Water Based

CAUTION

- Do not apply below 10°C or above 45°C.
- Do not apply if humidity > 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain paint before use.
- In case of eye contact, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool, dry place.

CERTIFICATION

- Compliant to VOC requirement for paints for LEED rated buildings¹.
- UV Block as per QUV Test².
- No algal growth as per ASTM Test D5589-09 (2013)³.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in a sound condition.
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in V-groove and fill with cement/crack filler.
- Apply cement putty wherever needed to fill the dents and level the surface.
- Wipe it clean before the paint application.



APPLICATION

- ROLLER** For best results, use a Long Nap Felt Roller
- DILUTION** Dilute Aurus Regal Exteriors with 25% potable water

For re-painting^ (Paint & Primer):

STEP 1	FIRST COAT		4 hrs dry
STEP 2	SECOND COAT		4 hrs dry

For new masonry surface^:

STEP 1	1 COAT		3-4 hrs dry
STEP 2	2 COATS		4 hrs dry before recoat



PAINT & PRIMER

Aurus Regal Exteriors is specially formulated to blend the functions of a primer with the finish coat. Two coats of Aurus Regal Exteriors provide a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.

*When painting unpainted surfaces, a light shade over a previous dark shade or painting over oil based paint or distemper - a coat of JSW Exterior Wall Primer should be applied. Apply JSW Exterior Wall Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before the finish coat.

**Additional coats may be required for darker shades.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use a dust mask or a nose pad during application, sanding and clean up.
- Close the container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash the affected area with a soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants & trees near the painted surface.
- Prevent sharp objects or impacts that damage the paint film.
- Ensure proper cleaning of the surface at an interval of 6 months.

PRODUCT INFORMATION

Colours	White
Tint Bases	AE-1, AE-2, AE-3, AE-4, AE-V, AE-M

KEY DATA

No. of colours	1808 shades (Ask for Colourvista Shade Panorama fandeck)
Coverage [^]	55 - 65 sq.ft./L/2coats 5.1 - 6 m ² /L/2coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	2 - 7 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Potable Water (up to 25%)
VOC levels~	<20 gms/L

Other Aurus products:

JSW Paints Aurus Range offers high performance emulsions for interior and exterior walls, providing a beautiful experience of painting spaces.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS



REGAL INTERIORS SILK



REGAL EXTERIORS SILK



REGAL EXTERIORS TILE COAT



REGAL EXTERIORS FLOOR COAT



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 curated shades.
- Tone-based user-friendly fandeck.
- Easy-to-choose colour combinations.

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Resistance to Ultra Violet Radiation as per ASTM D4587-11, when tested as per QUV exposure to ultra violet radiation for the duration of 1000 hours as per Internal Lab Test results. ³No algal growth when tested as per ASTM D5589 -09 (2013) for Determining the resistance of Paint Films to Algae Defacement as tested at Biotech Testing Services, Mumbai.

Version No. 02 (09/2024).

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager, JSW Paints Limited, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988.