



Halõ

MAJESTIC INTERIORS
LuxGlo



Halo Majestic Interiors LuxGlo, is a state-of-the-art emulsion for interior walls with a satin finish where design expertise offers best-in-class quality with low VOC. This water-based acrylic emulsion delivers excellent durability, washability and stain resistance to bring the promise of long lasting beauty alive.

Experience Halo Majestic Interiors LuxGlo -
Carefully crafted for a rich glow like finish.

PACK SIZES



GLOSS LEVEL



FEATURES

- Germ Block - Kills 99.9% of bacteria, fungi, and virus. Paint and primer.
- Low VOC.
- Excellent stain resistance.
- Anti-fungal.
- Endures 9 years.
- Superior opacity.
- Elegant sheen.
- Excellent smooth finish.
- Fast and easy to finish.
- Roller friendly paint.

CAUTION

- Do not apply below 10°C or above 45°C.
- Do not apply if humidity > 85%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain paint before use.
- In case of eye contact, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool and dry place.

CERTIFICATION

- Compliant to VOC requirement for paints for LEED rated buildings¹.
- Compliant to GRIHA standards for Low VOC².
- Compliant to JIS test for anti-microbial activity³.
- No fungal growth as per ASTM Test D5590:2017⁴.
- Resistance to household stains as per ASTM Test D4828-94(2016)⁵.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and wash thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in V-groove and fill with cement/crack filler.
- Apply cement/acrylic putty wherever needed to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper No. 320 and wipe clean before paint application.



APPLICATION

- ROLLER** For best results, use a Short Nap Felt Roller.
- DILUTION** Dilute Halo Majestic Interiors with 25% clean water.

For Repainting^ (Paint & Primer):

STEP 1	FIRST COAT	Halõ MAJESTIC INTERIORS LuxGlo	4 hours dry.
STEP 2	SECOND COAT	Halõ MAJESTIC INTERIORS LuxGlo	4 hours dry.

For New Masonry Surface^:

STEP 1	1 COAT	Wall Primer INTERIORS	3-4 hours dry.
STEP 2	2 COATS	Wall Putty ACRYLIC BASED	6-8 hours dry before recoat.
STEP 3	1 COAT	Wall Primer INTERIORS	3-4 hours dry.
STEP 4	2 COATS	Halõ MAJESTIC INTERIORS LuxGlo	4 hours dry before recoat.



PAINT & PRIMER

Halo Majestic Interiors is specially formulated to blend the functions of a primer with the finish coat. Two** coats of Halo Majestic Interiors provides a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.*

*When painting unpainted surfaces, light shade over previous dark shade, painting over oil based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Apply JSW Interior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3 to 4 hours before finish coat.

**Additional coats may be required for darker shades.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water.
- Get medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- Always remove any wall stains immediately from the walls.
- Remove all dirt using a clean cloth or duster. Always remove dirt from top to bottom. This helps in avoiding loose dirt to smudge the walls.
- For household stains like pencil, tea, coffee, crayons, turmeric, ketchup, sketch pen etc., use liquid dish wash/mild detergent solution. Use a sponge to remove the stains. Wipe the area with a clean cloth.

PRODUCT INFORMATION

Colours	White
Tint Bases	HLI-1, HLI-3, HLI-4, HLI-V, HLI-M

KEY DATA

No. of colours	1808 shades (Ask for Colourvista Shade Panorama fandeck.)
Coverage [^]	140-160 sq.ft./L/2 coats 13-14.9 m ² /L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	60-70 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (upto 25%)
VOC levels~	<10gms/L

Other Halõ products:

JSW Paints Halo Range offers best-in-class emulsions for Exterior Walls, eco-friendly water based enamels - Aquaglo for Wood & Metal and a fresh range of fragrances for a beautiful experience of painting spaces.

Carefully crafted for a glorious feel. The Halo Fresh range of fragrance additives lends a fresh, new feel that makes a home feel airy, beautiful and as good as new.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



MAJESTIC INTERIORS



MAJESTIC EXTERIORS



MAJESTIC EXTERIORS LUXGLO



EXCEED TOPCOAT



EXCEED BASECOAT



FRESH MAJESTIC FRAGRANCES



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 curated shades.
- Tone-based user-friendly fandeck.
- Easy-to-choose colour combinations.

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai. ³Compliant to Japanese Industrial Standard - JIS Z 2801: 2010 'Test for Anti-Bacterial Activity and Efficacy' as tested at Biotech Testing Services, Mumbai. ⁴No fungal growth when tested as per ASTM D5590: 2017 for 'Determining the Resistance of Paint Films to Fungal Defacement' as tested at Biotech Testing Services, Mumbai. ⁵Resistance to stains when tested as per ASTM D4828: 94 (2012) for relative ease of removal of common soil and stains from interior coatings as tested at National Test House, Mumbai.

Version No. 01 (04/2019.)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd., Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988