



Aur^{us}

REGAL INTERIORS



Aurus Regal Interiors Lustre, is a high performance emulsion for interior walls with a Pearl like lustre finish which brings colours to life. Thoughtfully designed to provide superior performance and application properties, it delivers exceptional dana pattern with a Mid Nap Felt Roller or Honeycomb Roller.

Experience Aurus Regal Interiors Lustre - "Thoughtfully designed for Pearl like Lustre and Rich Durable finish."

PACK SIZES



GLOSS LEVEL



FEATURES

- Endures 6 years*
Paint & Primer*
- Excellent Washability
- Anti-Fungal
- Rich Sheen
- Exceptional Dana Pattern
- Low VOC
- Water Based
- Superior Opacity
- Excellent finish
- Fast and easy to paint
- Roller friendly paint

CAUTION

- Do not apply below 10°C or above 45°C.
- Do not apply if humidity > 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain paint before use.
- In case of eye contact, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool, dry place.

CERTIFICATION

- Compliant to VOC requirement for paints for LEED rated buildings¹.
- Compliant to GRIHA standards for Low VOC².
- No fungal growth as per ASTM Test D5590:2017³.

PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in a sound condition.
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in V-groove and fill with cement/crack filler.
- Apply cement/acrylic putty wherever needed to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper No. 320 and wipe it clean before the paint application.

APPLICATION

- ROLLER** For best results, use Mid Nap Felt Roller / Honeycomb Roller.
- DILUTION** Dilute Aurus Regal Interiors Lustre with 10% potable water.

For repainting^ (Paint & Primer):

STEP 1	FIRST COAT		Aurus REGAL INTERIORS LUSTRE	4 hrs dry.
STEP 2	SECOND COAT		Aurus REGAL INTERIORS LUSTRE	4 hrs dry.

For new masonry surface^:

STEP 1	1 COAT		Wall Primer INTERIORS	3-4 hrs dry.
STEP 2	2 COATS		Wall Putty ACRYLIC BASED	6-8 hrs dry.
STEP 3	1 COAT		Wall Primer INTERIORS	3-4 hrs dry before recoat.
STEP 4	2 COATS		Aurus REGAL INTERIORS LUSTRE	4 hrs dry before recoat.

PAINT & PRIMER

Aurus Regal Interiors Lustre is specially formulated to blend the functions of a primer with the finish coat. Two coats of Aurus Regal Interiors Lustre provides a sturdier coat than the conventional 'Primer + 2 Finish coats' system, bringing your vision to life in quick time with less effort.*

*When painting unpainted surfaces, a light shade over a previous dark shade or painting over oil based paint or distemper - a coat of JSW Interior Wall Primer should be applied. Apply JSW Interior Primer over spots where spot putty/cement/crack filler is applied. Allow primer to dry for 3-4 hours before the finish coat.

**Additional coats may be required for darker shades.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use a dust mask or a nose pad during application, sanding and clean up.
- Close the container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash the affected area with a soap and plenty of water. Seek medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- Always remove any wall stains immediately from the walls.
- Remove all dirt using a clean cloth or a duster. Always remove dirt from top to bottom. This helps in avoiding loose dirt to smudge the walls.
- For household stains like pencil, tea, coffee, crayons, turmeric, ketchup, sketch pen etc., use liquid dish wash/mild detergent solution. Use a sponge to remove the stains. Wipe the area with a clean cloth.

PRODUCT INFORMATION

Colours	White
Tint Bases	AIL-1

KEY DATA

No. of colours	926 shades (Ask for Colourvista Shade Panorama fandeck)
Coverage [^] (With Mid Nap Felt Roller)	85 - 110 sq.ft./L/2 coats 7.8 - 10.2 m ² /L/2 coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	25 - 35 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Potable Water (upto 10%)
VOC levels~	<20 gms/L

Other Aurus products:

JSW Paints Aurus Range offers high performance emulsions for interior and exterior walls, providing a beautiful experience of painting spaces.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS



REGAL EXTERIORS



REGAL EXTERIORS TILE COAT



REGAL INTERIORS SILK



REGAL EXTERIORS SILK



REGAL EXTERIORS FLOOR COAT



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandeck is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 curated shades.
- Tone-based user-friendly fandeck.
- Easy-to-choose colour combinations.

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai. ²Compliant to GRIHA (Green Rating for Integrated Habitat Assessment) Criterion 26 on Low VOC Interior Paints as tested at National Test House, Mumbai. ³No fungal growth when tested as per ASTM D5590: 2017 for 'Determining the Resistance of Paint Films to Fungal Defacement' as tested at Biotech Testing Services, Mumbai.

Version No. 02 (09/2024).

This information sheet supersedes all previous versions.

For feedback/complaints, write to Customer Care Manager, JSW Paints Limited, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988.