



Aurus

REGAL EXTERIORS

Tile Coat



Aurus Regal Exteriors Tile Coat is a high-performing coating specially designed to protect roof tiles from extreme weather conditions. It is water-repellent, provides strong UV resistance, has a high sheen finish, and is available in a multitude of vibrant colours.

Experience Aurus Regal Exteriors Tile Coat - *"Carefully innovated to protect the finish of your tiles."*

PACK SIZES



GLOSS LEVEL



FEATURES

- Endures 6 years*
- Water Repellent
- High Sheen
- Anti Algal
- UV Resistant
- Paint & Primer*
- Low VOC
- Tough and durable film
- Bright Finish
- Fast and easy to finish
- Roller Friendly

CAUTION

- Do not apply at temperatures below 10°C and over 45°C.
- Do not over-thin. Use thinned paint within 24 hours.
- Tightly close the lid when not in use and store in a cool, dry place.
- Flaky, powdery substrate should not be painted on directly.
- Not recommended on glazed, non-porous, or very smooth tiles.
- Do not apply on surfaces that are subject to seepage or leakage issues without arresting the water source.
- Areas prone to algae growth will require an additional coat for better protection.



CERTIFICATION



- Compliant to VOC requirement for Paints for LEED rated buildings¹.
- UV test results as per inhouse testing on QUV machine.



PREPARATION

- Ensure that the surface to be painted is free from any damp or loose paint, dust, oil, wax, grease or any other contaminants.
- Remove all contaminants such as dirt, grease, oil, dust, efflorescence, laitance, etc., with soap-powder solution using a Scrubbing Brush. Remove algae and fungus from affected area. Dry for a minimum of 4-6 hours before painting. Moisture content on the surface should be less than 16%.
- Leaks and cracks causing constant dampness on roof tiles/surface should be corrected before painting.
- Check random areas for adhesion of existing paint film in case of repainting. If problems are observed, total removal of old paint is required.
- Tiles with surface imperfections such as holes, dents, and cracks are to be avoided. Use of any kind of putty is not recommended.
- Use of any kind of primer is not recommended.



APPLICATION

- ROLLER** Apply with Long Nap Felt Roller or Brush as a priming coat.
- DILUTION** Dilute Aurus Regal Exteriors Tile Coat with 25% potable water.

For new masonry surface[^]:

| | | | |
|--------|--------|---|-------------|
| STEP 1 | 1 COAT |  | 4-6 hrs dry |
| STEP 2 | 2 COAT |  | 4-6 hrs dry |

For better hiding, third coat can be applied similarly. Horizontal surfaces are painted with an additional coat for better protection.



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

POST PAINTING CARE

- Prevent water stagnation and overgrowth of plants and trees near painted surface.
- Prevent sharp objects or impacts that could damage paint film.
- For best performance, ensure proper washing and cleaning of the painted surface at regular interval of 6 months. Do not wash the surface with a metal wire brush.

PRODUCT INFORMATION

Tint Bases

AET-4

KEY DATA

| | |
|---------------------------------|---|
| No. of colours | 19 shades (Ask for Colourvista Aurus Tile Coat and Floor Coat Shade Card) |
| Coverage [^] | 100-120 sq.ft./L/1 coat |
| Drying Time* (30°C @ 60 R/H) | Surface Dry - 6-8 hours Recoat - 4-6 hours |
| Flash Point | N/A |
| Sheen Level | 25-30 units @ 60° GH |
| Vehicle Type | Acrylic |
| Thin with | Potable Water (upto 25%) |
| VOC levels~ | <20 gms/L |

Other Aurus products:

JSW Paints Aurus Range offers high performance emulsions for interior and exterior walls, providing a beautiful experience of painting spaces.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts into reality. Everything about the paint, its application, and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS



REGAL EXTERIORS



REGAL INTERIORS SILK



REGAL EXTERIORS SILK



REGAL EXTERIORS FLOOR COAT



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandek is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandek
- Easy to Choose Colour Combinations

¹Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai.

Version No.02 (02/2025)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paints Ltd., Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988