



# Aurus

REGAL EXTERIORS  
Floor Coat



Aurus Regal Exteriors Floor Coat is a specially designed emulsion for paver blocks and cement surfaces, providing high wear resistance to withstand light vehicles and human foot traffic. Additionally, its strong anti-algal property provides excellent protection to help maintain long-lasting beauty of cement surfaces.

Experience Aurus Regal Exteriors Floor Coat - *"Thoughtfully designed to protect your floor's' finish."*

## PACK SIZES



1 L

4 L

10 L

## GLOSS LEVEL



MATT

SILK

SATIN

GLOSS

## FEATURES

- Wear Resist
- Anti-algal
- UV Resist
- Endures 2 years\*
- Water Repellent
- High Sheen
- Paint & Primer\*
- Low VOC
- Bright finish
- Fast and easy to finish
- Roller friendly paint
- Water Based

## CAUTION

- Do not apply at temperatures below 10°C and over 45°C.
- Do not over-thin. Use thinned paint within 24 hours.
- Tightly close the lid when not in use and store in a cool, dry place.
- Flaky, powdery substrate should not be painted without proper re-plastering.
- Do not apply on Bituminous, Asphalt, ceramic tiles, or glossy substrate.
- Use on porous cement or ash brickwork can result in the coating peeling from substrate.
- Do not apply on surfaces that are subject to continuous seepage or dampness.
- Improper levelling of paver blocks/surface, which will lead to erosion of substrate and paint, should be levelled properly before application of paint.



## CERTIFICATION



- Compliant to VOC requirement for Paints for LEED rated buildings<sup>1</sup>.
- UV test results as per inhouse testing on QUV machine.



## PREPARATION

- Ensure that the surface to be painted is free from any damp or loose paint, dust, oil, wax, grease or any other contaminants.
- Remove all contaminants such as dirt, grease, oil, dust, etc., with soap-powder solution using a Scrubbing Brush and Jet Wash. Remove algae or fungus from affected area. Dry for a minimum of 4-6 hours before painting. Moisture content on the surface should be less than 16%.
- For freshly made concrete surface, allow it to cure for at least 4 weeks before painting.
- Check random areas for adhesion of existing paint film. If problems are observed, total removal of old paint is required.
- Sand smooth, glossy surfaces and the surfaces previously coated with solvent-based paints with sandpaper no. 120 to improve adhesion.



## APPLICATION

- ROLLER** Apply with Long Nap Felt Roller or Brush.
- DILUTION** Dilute Aurus Regal Exteriors Floor Coat with 10% potable water.

For new masonry surface^:

STEP 1	1 COAT		4-6 hrs dry
STEP 2	2 COAT		4-6 hrs dry

Depending upon the surface, third coat of paint may be applied for better hiding



## INFORMATION AND CARE

### ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not breathe spray mist or sanding dust.
- Use dust mask or nose pad during application, sanding and clean up.
- Close container after each use.
- Wash thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals.

### POST PAINTING CARE

- Prevent water stagnation and overgrowth of plants and trees near the painted surface.
- Prevent sharp objects or impacts that could damage paint film.
- Allow at least 48 hours of curing before foot traffic begins. Regular traffic can begin only after 72 hours of curing. Duration given for drying must be extended in cold, damp, or humid conditions.
- Avoid movement of heavy vehicles and heavy sharp objects, this may rupture the film and lead to film failure.
- For best performance, ensure proper washing and cleaning of the painted surface every 6 months.
- Do not wash the painted surface with a metal wire brush.

## PRODUCT INFORMATION

Colours	White, Terra Power, Javelin Gold, Nadir
Tint Bases	AEF-4

### KEY DATA

No. of colours	21 shades (Ask for Colourvista Aurus Tile Coat and Floor Coat Shade Card)
Coverage <sup>^</sup>	40-50 sq.ft./L/1 coat
Drying Time* (30°C @ 60 R/H)	Surface Dry - 6-8 hours Recoat - 4-6 hours
Flash Point	N/A
Sheen Level	25-30 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Potable Water (upto 10%)
VOC levels-	<20 gms/L

## Other Aurus products:

JSW Paints Aurus Range offers high performance emulsions for interior and exterior walls, providing a beautiful experience of painting spaces.

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.



REGAL INTERIORS



REGAL EXTERIORS



REGAL INTERIORS SILK



REGAL EXTERIORS SILK



REGAL EXTERIORS TILE COAT



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandek is uniquely designed to easily pick the right colour and choose colour combinations for homes.



Colourvista Shade Panorama

### FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandek
- Easy to Choose Colour Combinations

<sup>1</sup>Compliant to LEED (Leadership in Energy & Environmental Design) VOC criteria as per IGBC (Indian Green Building Council) as tested at National Test House, Mumbai.

Version No.02 ( 02/2025)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paints Limited, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai 400 026, India or email at [ccpaints@jsw.in](mailto:ccpaints@jsw.in) or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

-VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988