



Profect

MAJESTIC EXTERIORS



Profect Majestic Exterior is an ultra-premium, high performance water based acrylic emulsion for exterior surfaces, that provides unparalleled protection from the harshest weather conditions. Powered with a combination of unique additives, it gives unmatched protection from rough weather condition, dirt resistance and algal growth. It gives ultimate protection to your project, with an endurance of 7 years.

PACK SIZES



20 L

GLOSS LEVEL



FEATURES



- Weather resistant
- Anti-algal
- Dirt resistant
- Elegant sheen
- Excellent opacity
- Low VOC

SURFACES



New or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good coverage and weather protection is desired with bright finish.

CAUTION



Do not apply if temperature is below 10°C or above 45°C.

Do not apply if humidity is greater than 90%.

Do not over-thin paint. Use thinned paint within 24 hours.

Shake, stir and strain the paint before use.


In case of eye contact, wash with plenty of water.

Tightly close the lid when not in use and store in a cool, dry place.



PREPARATION

- Surfaces to be painted must be clean, dry, and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement / crack filler, and apply cement putty (wherever needed) to fill the dents and level the surface.
- Wipe clean before paint application.



APPLICATION

- Apply one coat of Profect Primer Exterior over entire surface.
- Allow primer to dry for 3-4 hours before finish coat.
- Dilute paint with 40-50% potable water and apply 2 coats with long nap felt roller, at an interval of 3-4 hours over properly prepared bare or painted exterior surfaces.
- Dark shades may require additional finishing coats.



INFORMATION AND CARE

HEALTH, SAFETY, SECURITY AND ENVIRONMENT

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from edible items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not pour paint waste in water courses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

POST PAINTING CARE

- Prevent water stagnation, overgrowth of plants & trees near the painted surface.
- Prevent sharp objects or impact that may damage the paint film.
- Ensure proper cleaning of the surface at every 6 months.

PRODUCT INFORMATION

Colours	White
Tint Bases	PME 1, PME 2, PME 3

KEY DATA

No. of colours	1441 shades (Ask for Colourvista Shade Panorama fan deck)
Coverage [^]	55 - 60 sq.ft./L/2coats 5.57 - 6.03 m ² /L/2coats
Drying Time* (30°C @ 60 R/H)	Surface Dry - 30 minutes Recoat - 4 hours
Flash Point	N/A
Sheen Level	12 - 15 units @ 60° GH
Vehicle Type	Acrylic
Thin with	Clean Water (40 - 50%)
VOC levels-	Low

The Prōfect Range:



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



ELEGANT EXTERIORS



JSW Paints presents Colourvista Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourvista Shade Panorama Fandek enables you to easily pick the right colour and choose colour combinations for your projects.



Colourvista Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based user-friendly Fan deck
- Easy to Choose Colour Combinations

Version No. 01 (07/2020)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.