



Profect

WALL PRIMER INTERIORS



Profect Wall Primer Interiors is a high-performing undercoat that is essential to prepare your interior walls for the paint job. It offers high opacity and good coverage, and is hence, the right choice for the best top-coat performance. Suitable for all masonry applications, this undercoat provides the perfect base for a rich, smooth, even, and longer-lasting finish.

PACK SIZES



20 L

GLOSS LEVEL



MATT



SILK



SATIN



GLOSS

FEATURES



High-bonding
High-opacity
Good coverage
Quick-drying
Water-based

SURFACES



New or previously painted wall, plastered and prepared masonry surfaces.

CAUTION



Do not apply if temperature is below 10°C or above 45°C.

Do not apply if humidity is greater than 90%.

Do not over-thin paint. Use thinned paint within 24 hours.

Shake, stir and strain the paint before use.

In case of eye contact, wash with plenty of water.

Tightly close the lid when not in use and store in a cool, dry place.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in the V-groove and fill with cement/crack filler. Prime the entire surface with Profect Wall Primer Interiors.
- Apply cement/acrylic putty (where needed) to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper no.320, and wipe it clean before paint application.



APPLICATION

1. Dilute JSW Paints Profect Wall Primer Interiors with 100% clean water.
2. Apply 1 coat of JSW Paints Profect Wall Primer Interiors, and leave it to dry for 3 to 4 hours.
3. Apply 1 coat of Wall Putty, and leave it to dry for 6 to 8 hours.
4. Sand to smoothen putty surface, and wipe surface to remove dust.
5. Apply 1 coat of JSW Paints Profect Wall Primer Interiors, and leave it to dry for 3 to 4 hours.



INFORMATION AND CARE

HEALTH, SAFETY, SECURITY AND ENVIRONMENT

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from edible items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not pour paint waste in water courses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

POST PAINTING CARE

- Apply finishing coat within 7 days of primer application.

PRODUCT INFORMATION

Colours

White

KEY DATA

Coverage[^]

180 - 220 sq.ft./L/coats

16.7 - 20.4 m²/L/coats

Drying Time*
(30°C @ 60 R/H)

Surface Dry - 30 minutes

Recoat - 4 hours

Flash Point

N/A

Sheen Level

Matt 0 - 10 units @ 60° GH

Vehicle Type

Acrylic

Thin with

Clean Water (100%)

VOC levels~

Low

The Prōfect Preparation Products:

Prōfect Preparation Range offers optimum base for the painting surface. So as to ensure that the finishing coats provide a beautiful experience of painting spaces.



WALL PRIMER EXTERIORS

JSW Paints Prōfect Top Coats Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



MAJESTIC EXTERIORS



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



ELEGANT EXTERIORS

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way of making projects beautiful.

Version No. 01 (08/2020)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.