



Profect

REGAL INTERIORS



JSW Paints Profect Regal Interiors is a high-performance water-based modified acrylic emulsion for interior walls with a rich matt finish. It provides superior performance, excellent hiding and best-in-class coverage.

Its unique formula enables colour to last longer. It is suitable for all normal interior masonry surfaces including particle board, fiber and insulation boards.



20 L

PACK SIZES

GLOSS LEVEL



FEATURES



- Superior Washability
- Anti Algal
- 6 Years Warranty*
- Water Based
- Low VOC
- Modified Acrylic
- Rich Matt Finish

SURFACES



For new or previously painted walls, plastered and prepared masonry surfaces. Ideal for surfaces where good durability and superior coverage is desired with a bright finish.

CAUTION



- Do not apply below 10 °C or above 45 °C.
- Do not apply if humidity is greater than 90%.
- Do not over-thin. Use thinned paint within 24 hours.
- Shake, stir and strain the paint before use.
- In case of contact with eyes, wash with plenty of water.
- Tightly close the lid when not in use and store in a cool, dry place.



PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure for 28 days before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growths of fungus, algae or moss should be removed by wire brushing, and washing thoroughly with potable water.
- In case of areas with excess dampness, please repair the surface before applying paint.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in a V-groove and fill with cement / crack filler. Prime the entire surface with Profect Primer Interior.
- Apply cement/acrylic putty (wherever needed) to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper No. 320 and wipe it clean before paint application.



APPLICATION

- Apply one coat of JSW Paints Profect Primer Interior over the entire surface.
- Allow primer to dry for 3-4 hours before applying the finish coat.
- Smoothen the surface with sandpaper No. 320 and wipe it clean.
- Dilute paint with 40-50% potable water and apply two coats with Short Nap Felt Roller at an interval of 3-4 hours over properly prepared bare or painted interior surfaces.
- Dark shades may require additional finish coats.



INFORMATION AND CARE

HEALTH, SAFETY, SECURITY AND ENVIRONMENT

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from edible items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, immediately wash with soap and plenty of water. Seek medical attention if irritation develops or persists.
- Do not pour paint waste in water courses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

POST PAINTING CARE

- Prevent sharp objects, or impact that may damage the paint film.
- Ensure proper cleaning of surface at an interval of every 6 months.

PRODUCT INFORMATION

Tint Bases

PRI 1

KEY DATA

No. of colours

900+ shades
(Ask for Colourv^{ista} Shade
Panorama Fan deck)

Coverage[^]

110 - 120 sq.ft./L/2coats
10.2 - 11.14 m²/L/2coats

Drying Time*
(30°C @ 60 R/H)

Surface Dry - 30 minutes
Recoat - 4 hours

Flash Point

N/A

Sheen Level

2 - 5 units @ 60° GH

Vehicle Type

Modified Acrylic

Thin with

Clean Water (upto 40 - 50%)

VOC levels-

Low

Other Prōfect Products:



ELEGANT INTERIORS



ELEGANT EXTERIORS



MAJESTIC EXTERIORS



REGAL EXTERIORS



JSW Paints presents Colourv^{ista} Shade Panorama, a splendid collection of 1808 curated shades assembled in tones for every mood. The Colourv^{ista} Shade Panorama Fandek enables you to easily pick the right colour and choose colour combinations for your projects.



Colourv^{ista} Shade Panorama

FEATURES OF THE INNOVATIVE FANDECK

- 1808 Curated Shades
- Tone Based User-friendly Fandek
- Easy to Choose Colour Combinations

Version No. 02 (04/2026)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

[^]Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.