



# Profect

WALL PRIMER ECO INTERIORS



Profect Wall Primer Eco Interiors is a perfect base coat for interior walls that need to be prepared for painting with water-based wall finishes such as distempers and emulsion paints. It provides excellent coverage and opacity, making it the perfect choice for achieving a rich, smooth, and long-lasting top coat finish.

Profect Wall Primer Eco Interiors – *Bright white primer for interior walls*



20 L

PACK SIZES

GLOSS LEVEL



## FEATURES



BRIGHT WHITE



GOOD OPACITY



GOOD COVERAGE



QUICK DRYING



ECONOMICAL



WATER THINNABLE

## CAUTION

Do not apply if temperature is below 10°C or above 45°C.

Do not apply if humidity is greater than 80%.

Do not over-thin paint. Use thinned paint within 24 hours.

Shake, stir and strain the paint before use.

In case of eye contact, wash with plenty of water.

Tightly close the lid when not in use and store in a cool, dry place.



## PREPARATION

- Surfaces to be painted must be clean, dry and free from seepage, leakage, loose old paint, dirt, dust, grease, oil, soap, wax and other impurities.
- Remove any peeling paint and sand these areas to feather the edges smooth with adjacent surfaces.
- New plaster or masonry surfaces must be allowed to cure (28 days) before application.
- Cured plaster should be hard (non-powdery) and in sound condition.
- Growth of fungus, algae or moss should be removed by wire brushing and washing thoroughly with potable water.
- In case of areas having excess dampness, please repair the surface before painting.
- In case there are structural cracks, please study and repair them with a structural engineer.
- Open non-structural cracks in the V-groove and fill with cement/crack filler. Prime the entire surface with Profect Wall Primer Eco Interiors.
- Apply cement/acrylic putty (where needed) to fill the dents and level the surface.
- Sand and smoothen the surface with sandpaper no.320, and wipe it clean before paint application.



## APPLICATION

**SURFACES** New or previously painted wall, plastered and prepared masonry surfaces

**TOOLS** For best results, use a Short Nap Felt Roller

**DILUTION** Dilute Profect Wall Primer Eco Interiors with 100% clean potable water

## APPLICATION PROCESS

STEP 1	1 COAT	Profect Wall Primer ECO INTERIORS	3-4 hrs drying
STEP 2	1 COAT	Profect Wall Putty CEMENT BASED	6-8 hrs drying
STEP 2	1 COAT	Profect Wall Putty CEMENT BASED	6-8 hrs drying before re-coat, light sanding after drying with 180 mesh sand paper
STEP 3	1 COAT	Profect Wall Primer ECO INTERIORS	3-4 hrs drying



## INFORMATION AND CARE

### HEALTH, SAFETY, SECURITY AND ENVIRONMENT

- Use only with adequate ventilation during application and drying.
- Avoid contact with eyes and prolonged or repeated contact with skin.
- Do not inhale the spray mist or sanding dust.
- Use a dust mask or nose pad during application, sanding and clean-up process.
- Close the container after each use and store in a cool and dry place, in an upright position.
- Keep out of reach of children and away from edible items.
- Do not use empty containers as means to store food.
- Seek immediate medical attention if paint is ingested or swallowed by mistake.
- Wash skin thoroughly after handling.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not pour paint waste in water courses or in common waste. Needs to be recycled or disposed as per hazardous waste management rules.
- No added Lead, Mercury, Chromium, Arsenic or any other heavy metals.

### POST PAINTING CARE

- Apply finishing coat within 7 days of primer application.

## PRODUCT INFORMATION

Colours

White

### KEY DATA

Coverage<sup>^</sup>

180 - 220 sq.ft./L/coats

16.7 - 20.4 m<sup>2</sup>/L/coats

Drying Time\*  
(30°C @ 60 R/H)

Surface Dry - 30 minutes

Recoat - 4 hours

Flash Point

N/A

Sheen Level

Matt 0 - 5 units @ 60° GH

Vehicle Type

Modified Acrylic

Thin with

Clean Potable Water (100%)

VOC levels~

Low

## The Prōfect Preparation Products:

Prōfect Preparation Range offers optimum base for the painting surface. So as to ensure that the finishing coats provide a beautiful experience of painting spaces.



PROFECT WALL PUTTY



WALL PRIMER ECO EXTERIORS



WALL PRIMER EXTERIORS



WALL PRIMER INTERIORS



TEXTURE

## JSW Paints Prōfect Top Coats Range:

Our extensive range of water-based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



MAJESTIC EXTERIORS



REGAL INTERIORS



REGAL EXTERIORS



ELEGANT INTERIORS



ELEGANT EXTERIORS



CLASSIC INTERIORS

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way of making projects beautiful.

Version No. 01 (03/2022)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G.Deshmukh Marg, Mumbai - 400 026, India, or email at ccpaints@jsw.in or call on 1800-121-5797.

\*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

<sup>^</sup>Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.