



iBlok

CRACK FIX



JSW Paints iBlok Crack Fix paste is a water based, ready to use Crack paste for Interiors & Exteriors Surfaces. It provides strong crack bridging ability for Plaster cracks of up to 3 mm.

Its advanced technology gives excellent filling and binding properties.

Placeholder



350 G



900 G

PACK SIZES

GLOSS LEVEL: N/A

FEATURES



- Elastomeric
- Crack Sealing
- Water proofing
- Strong Adhesion
- Ready to use

SURFACES



Plastered Ext Walls
Plastered Int Walls

CERTIFICATION



As per ASTM D 2370, the film passes Elongation test of 555%

CAUTION



Do not apply below 10 °C or above 45 °C

Do not apply if humidity > 90%

In case of eye contact, wash with plenty of water, seek medical attention

Tightly close the lid when not in use and store in a cool, dry place



PREPARATION

- Remove all loose paint, fungus & algae with wire brush and thoroughly clean with water
- Open the cracks using a cutter and widen them to form 'V' shaped groove. Clean the dust and loose particles from the groove
- Apply JSW Wall Primer in opened cracks using a brush. Use JSW Wall Primer Interiors on interior surfaces and JSW Wall Primer Exteriors on exterior surfaces with recommended dilution



APPLICATION

- Apply first coat of i-Blok WaterStop Crack Fix using putty knife/trowel. Penetrate the material inside the crack
- Allow drying of 6-8 hours and apply second coat for levelling
- Post drying, use JSW Wall Putty - Cement based to level the surface for interior surfaces
- Appropriate primer application and finish coat to be applied

PUTTY KNIFE For best results, use a quality putty knife

DILUTION Dilution not required

RECOMMENDED SYSTEM OF APPLICATION

STEP 1	1 COAT	JSW Paints iBlok Crack fix Paste	6-8 hrs dry
STEP 2	1 COAT	JSW Paints iBlok Crack fix Paste	6-8 hrs dry 6 to 8 hours drying, light sanding after drying with 180 mesh sand paper
STEP 3	1 COAT	JSW Paints Wall Putty Acrylic Based	6-8 hrs dry 6 to 8 hours drying, sanding after drying with 320 mesh sand paper
STEP 4	SANDING	Sand and smoothen the surface with sand paper no. 320 and wipe clean before paint application	
STEP 4	1 COAT	JSW Paints Wall Primer - Interior	6-8 hrs dry



INFORMATION AND CARE

ENVIRONMENTAL HEALTH AND SAFETY

- Use only with adequate ventilation during application and drying
- Avoid contact with eyes and prolonged or repeated contact with skin
- Do not breathe spray mist or sanding dust
- Close container after each use
- Wash thoroughly after handling
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists
- No added Lead, Mercury, Chromium, Arsenic and other heavy metals

POST PAINTING CARE

- Apply primer coat within 24-48 hrs of putty application
- Apply finishing coat within 7 days of primer application



PRECAUTION

- Do not apply on structural or joint cracks, i-Blok WaterStop Crack Fix is recommended for non-structural cracks only
- Ensure the surface is completely dry and free from dampness
- Do not apply for cracks of more than 3mm width
- Do not apply at temperature below 10°C and over 45°C and humidity greater than 90%
- In case of eye contact, wash with plenty of water. Take medical advice
- Tightly close the lid when not in use and store in a cool dry place

PRODUCT INFORMATION

Colours	White
KEY DATA	
Drying Time*	-
Flash Point	NA
Sheen Level	NA
Vehicle Type	Acrylic System
Thin with	Not required
VOC levels~	< 10 gm/Kg

For cracks on plastered surfaces (up to 3mm width and 5mm depth, we recommend 2 coats with 75 running ft/KG)

Other JSW Paints Waterproofing Products:

JSW Paints Waterproofing Range offers optimum base for the painting surface so as to ensure that the finishing coats provide a beautiful experience of painting spaces.



PRIME COAT



ROOFCOAT



WATERSTOP PRIME COAT

JSW Paints Top Coats Range:

Our extensive range of water based emulsions are designed to capture myriad ideas of beauty and evoke a spectrum of emotions that set the perfect ambience.



HALO INTERIOR



AURUS INTERIOR



PIXÁ INTERIOR

JSW Paints - Think Beautiful. Every JSW Paints product works to transform beautiful thoughts to reality. Everything about the paint, its application and finish is designed to be the 'Simple-Swift-Sure' way to making homes beautiful.

Version No. 01 (03/2022)

This information sheet supersedes all previous versions

For feedback/complaints, write to Customer Care Manager, JSW Paint Pvt. Ltd, Jindal Mansion, 5A, Dr. G. Deshmukh Marg, Mumbai 400 026, India or email at ccpaints@jsw.in or call on 1800-121-5797.

*Drying time and number of coats are dependent on temperature, humidity, surface porosity and film thickness.

^Actual coverage may vary from the quoted coverage, due to factors such as method and condition of application and surface roughness and porosity.

~VOC Levels as certified by NTH. Meets VOC as per BIS Standard - IS 101 (Part 2/Sec 2)/1986 & IS 101 (Part 2/Sec 1)/1988